



Wood Screws

Deep Thread with Type-17 Point

Flat Square Recess



FLAT SQUARE RECESS DEEP THREAD WOOD SCREW WITH TYPE-17 POINT

Nominal Diameter	A		R		D		T		Recess Size
	Head Diameter		Recess Depth		Major Diameter		Threaded Length		
	Max	Min	Max	Min	Max	Min	L ≤ 1"	L > 1"	
8	0.332	0.292	0.075	0.065	0.174	0.164	Full thread	2/3 thread	#2
Tolerance on Length	Up to 5/8"						+0 / -0.03		
	Over 5/8 to 1.5"						+0 / -0.05		
	Over 1.5 to 2.75"						+0 / -0.06		
	Over 2.75 to 5"						+0 / -0.09		

Description	An externally threaded fastener with a countersunk head, square socket recess and a single lead thread. The shank has a reduced diameter and a chip cavity cut out where the final several threads, ending at the tip.
Applications / Advantages	The deeper thread design offers greater resistance to pull-out forces. The chip cavity (or auger point) enables the fastener to drive—especially in denser woods—without pre-drilling a pilot hole.
Material	C1022 case-hardened steel
Surface Hardness	Rockwell C 45 minimim
Case Depth	0.004" - 0.009"
Torque	35 kg/cm minimum
Plating	See Appendix-A for plating information